

Yuken Vane



[Yuken vane](#) is double-sided circular section, Improve the lifetime of the stator and the vane, To reduce the noise. Yuken vane applied to the following types of pump:

1. Yuken single-pump series

PV2R1, PV2R2, PV2R3, PV2R4, 50T, 150T;

2. Yuken double-pump series

PV2R12, PV2R13, PV2R14, PV2R23, PV2R24, PV2R33, PV2R34.

Parameter:

1. Material : [SKH51, M2 , High Speed Steel](#)
2. Hardness : HRC 60° ~65°
3. Precision : 0.003~0.005mm or custom-made is acceptable
4. Surface Roughness: Ra<0.2
5. Suitable for PK Series

ZT International — **The most professional exporter on special steel**

Tel:+86-571-28903510

E-mail:marketing@zt-corp.com

Fax:+86-571-28903510

baron.dayuan@gmail.com

Skype: baron.dayuan

Web:http://www.zt-corp.com

ADD: A401,Oceanwide International Center,2# Xiangzhang Road, Hangzhou, Zhejiang, China 310018.

Thickness	Width	Length	Radius
2.200	17.000	30.000	+R1.8
1.800	8.000	22.000	+R1.5 +R1.2
1.800	8.000	30.000	+R1.5 +R1.2
1.800	10.000	30.000	+R1.5 +R1.2
1.800	10.000	37.000	+R1.5 +R1.2
2.400	18.000	55.000	+R1.8

ZT International — **The most professional exporter on special steel**

Tel:+86-571-28903510

E-mail:marketing@zt-corp.com

Fax:+86-571-28903510

baron.dayuan@gmail.com

Skype: baron.dayuan

Web:http://www.zt-corp.com

ADD: A401,Oceanwide International Center,2# Xiangzhang Road, Hangzhou, Zhejiang, China 310018.