

## Marine Motor Vane



Marine Motor Vane is mainly used for Crane and Winch Motor. There are 8pcs Marine Vane in the rotor slots. During the operation, Oil Pressure drives the rotor to run together with vanes. Marine Crane and Winch Motor Vanes are suitable for IHI models - HVB, HVN, HVK, HV-LL.

Material	Hardness	Thickness	Width	Length	Radius	Precision	Surface Roughness
9CrWMn	HRC 58°-62°	7.615	27	129.99	Acc.to Drawing	< 5μ	Ra < 0.4
9CrWMn	HRC 58°-62°	7.615	27	194.985	Acc.to Drawing	< 5μ	Ra < 0.4
50CrVA	HB363-429	7.84	39.5	189.96	Acc.to Drawing	< 10μ	Ra < 0.4
50CrVA	HB363-429	9.84	52	319.94	Acc.to Drawing	< 10μ	Ra < 0.4
50CrVA	HB363-429	16	100	450	Acc.to Drawing	< 10μ	Ra < 0.4

**ZT International — The most professional exporter on special steel**

Tel:+86-571-28903510

E-mail:marketing@zt-corp.com

Fax:+86-571-28903510

baron.dayuan@gmail.com

Skype: baron.dayuan

Web:http://www.zt-corp.com

ADD: A401,Oceanwide International Center,2# Xiangzhang Road, Hangzhou, Zhejiang, China 310018.